





Features	
<ul style="list-style-type: none"> Low profile, flat type relay Dimensions: 23.0×16.1×10.2(mm) Max. Switching capacity: 15A Tungsten lamp load: 10A 125VAC High sensitivity 200mW 	
Safety Approval	
NO.1460119	NO.CQC08002027612
NO.50116138	NO.E164730 NO.E322395



ORDERING INFORMATION



Remarks: 1. Available in 1 Form A only 2. Coil voltage 3 to 24VDC - Coil power: 200mw, 48VDC: 250mw

SPECIFICATION

CONTACT DATA

Contact Form	1 Form A	
Contact Material	Ag Alloy	
Contact Rating	15A125VAC 10A 250VAC/24VDC	
Contact Resistance	Max. 100mΩ (6VDC 1A)	
Load	Max. Switching Voltage	250VAC/30VDC
	Max. Switching Current	16A
	Max. Switching Power	4,000VA, 480W
	Min. Switching Load	5VDC, 100mA
Life	Electrical	100,000 operations
	Mechanical	10,000,000 operations

COIL DATA

Nominal Coil Power	200mW
--------------------	-------

GENERAL DATA

Insulation Resistance	Min. 1000MΩ 500VDC	
Dielectric Strength	Between open contacts	750VAC, 1min
	Between coil and contacts	2,500VAC, 1min
Operate Time	Max. 15ms	
Release Time	Max. 8ms	
Operating Temperature	-40°C to +85°C	
Humidity	35~95%RH, +40°C	
Shock Resistance	Endurance	1,000m/s ²
	Misoperation	100m/s ²
Vibration Resistance	Endurance	10~55Hz, 1.5mm double amplitude
	Misoperation	10~55Hz, 1.5mm double amplitude
Weight	Approximately 9.00g	

Note:Data shown are of initial value

SAFETY APPROVAL

File Number	Contact Form	Power Consumption	Coil Voltage	Contact Rating	Remarks
UL E164730	A	0.2W	3 - 48VDC	10A 250VAC	Class F Insulation Ambient Temperature: 105°C
				13A 125VAC	
				Tungsten lamp load:10A 125VAC	Class F Insulation Ambient Temperature: 85°C
				15A 125VAC	
UL E322395	A	0.2W	3 - 48VDC	TV-5 125VAC	Ambient Temperature: 85°C
				1/2HP 120VAC	

V6

POWER RELAY

SAFETY APPROVAL

File Number	Contact Form	Power Consumption	Coil Voltage	Contact Rating	Remarks
CSA 1460119	A	0.2W	3 - 48VDC	10A 250VAC	—
				Tungsten lamp load: 10A 125VAC	Ambient Temperature: normal
TUV 50116138-0001	A	0.2W	3 - 48VDC	16A 250VAC	Ambient Temperature: 85°C
				10A 30VDC	Ambient Temperature: 85°C
TUV 50116138-0002 (EN60730-1)	A	0.2W	3 - 48VDC	16(3)A 250VAC	Ambient Temperature: 85°C
CQC 08002027612 (GB/T 21711.1-2008)	A	0.2W	3 - 48VDC	16A 250VAC	Ambient Temperature: 85°C

Specifications subject to change without notice


COIL DATA

Ambient Temperature: 23°C

Model	Nominal Voltage VDC	Coil Resistance Ω +/-10%	Operate Voltage \leq VDC	Release Voltage \geq VDC	Coil Power mW
V6-S-DC3V	3	45	2.25	0.30	200
V6-S-DC5V	5	125	3.75	0.50	
V6-S-DC6V	6	180	4.5	0.60	
V6-S-DC9V	9	405	6.75	0.90	
V6-S-DC12V	12	720	9.0	1.20	
V6-S-DC24V	24	2880	18.0	2.40	
V6-S-DC48V	48	9216	36.0	4.80	250


OUTLINE, WIRING DIAGRAM, MOUNTING HOLE LAYOUT (UNIT: mm)

Outline




OUTLINE, WIRING DIAGRAM, MOUNTING HOLE LAYOUT (UNIT: mm)

Mounting Hole Layout
(Bottom View)




Wiring Diagram
(Bottom View)




REFERENCE DATA


Time Curve



Operating Range



Life Curves



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [General Purpose Relays](#) category:

Click to view products by [Zhejiang](#) manufacturer:

Other Similar products are found below :

[PCN-105D3MH,000](#) [59641F200](#) [5JO-1000CD-SIL](#) [5X827E](#) [5X837F](#) [5X840F](#) [5X842F](#) [5X848E](#) [LY2N-AC120](#) [LY2S-AC220/240](#) [LY2-US-AC120](#) [LY2-US-DC24](#) [LY3-US-AC120](#) [LY4F-UA-DC12](#) [LY4F-UA-DC24](#) [LY4F-US-AC120](#) [LY4F-US-AC240](#) [LY4F-US-DC24](#) [LY4F-VD-AC110](#) [LYQ20DC12](#) [M115C60](#) [M115N010](#) [M115N0150](#) [603-12D](#) [60HE1-5DC](#) [60HE2S-12DC](#) [61211T0B4](#) [61212T400](#) [61222Q400](#) [61243B600](#) [61243C500](#) [61243Q400](#) [61311BOA2](#) [61311BOA6](#) [61311BOA8](#) [61311C0A2](#) [61311COA1](#) [61311COA6](#) [61311F0A2](#) [61311QOA1](#) [61311QOA4](#) [61311T0D6](#) [61311TOA6](#) [61311TOA7](#) [61311TOB3](#) [61311TOB4](#) [61311U0A6](#) [61312Q600](#) [61312T400](#) [61312T600](#)