







N=PIN数



Material
 Insulator: Glass filled PBT,(UL 94V-0)
 Contact : Brass
 Surface Coating:GOLD Over Nickel

Electrical Characteristics
 Current rating:1.5Amps
 Dielectric Withstanding Voltage:AC 500V for 1 Minute.
 Insulator Resistance:1000MΩ Min.
 Contact Resistance:20mΩ Max.
 Operating Temperature:-40℃~+105℃



未注公差尺寸		
公差		
尺寸	长度	角度
X	±0.3	±5°
XX	±0.2	±3°
X.XX	±0.15	

DC3-2.54*PAS

上海洲日电子有限公司
 Shanghai Zhouri Electronics CO.,LTD
 上海康司玛电子设备进出口有限公司
 Shanghai KangSiMa Electronic Equipment
 import and export Co.,LTD
 TEL:86-21-34975176/51571121

绘图	周元金	201171018	物料编号	20171018 A/0
审核	张海娜	201171018		ZR20171018-178
核准	章妹	20181111		

1:1 mm 图幅 A4

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [ZHOURI](#) manufacturer:

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)
[820-22-008-30-001101](#) [821-22-002-10-001101](#)