



材料Material  
 原料Insulator:PBT,(UL 94V-0)  
 相关材料Related Material: Brass  
 表面涂层Surface Coating:Over Nickel

规格Specification  
 额定电流Current rating:1.5AMP  
 耐压Dielectric Withstanding Voltage:1000v Ac Min  
 绝缘电阻Insulation Resistance:1000MΩ min  
 接触电阻Contact resistance:30MΩ Max  
 工作温度Operating Temperature:-45℃~+105℃

1	Dimension (mm)	
	A	B
6	5.08	12.32
8	7.62	14.86
10	10.16	17.40
12	12.70	19.94
14	15.24	22.48
16	17.78	25.02
20	22.86	30.10
24	27.94	35.18
26	30.48	37.72
30	35.56	42.80
34	40.64	47.88
40	48.26	55.50
50	60.96	68.20
60	73.66	80.90
64	78.74	85.98

		上海洲日电子有限公司	
		Shanghai Zhouri Electronics CO.,LTD	
		上海康司玛电子设备进出口有限公司	
		Shanghai KangSiMa Eletronic Equipment import and export Co.,LTD	
绘图:	MAXIA	日期:	20170320
审核:	FANHUA	日期:	20170320
版本编号:	ZRLCGY2015-05-01-CJ		
tel:021-51571121		http://www.zhouri.net	
fax:021-51571120		http://www.ksmchian.com	
产品名称:		FC-2.54-*P	
第三视角:	单位: mm	比例:	图幅:A4 页次 共 01 第 01

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [ZHOURI](#) manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)  
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)  
[820-22-008-30-001101](#) [821-22-002-10-001101](#)