

3R Ceramic Surge Arresters

SPECIFICATION

Changzhou Wujin Jiangnan Discharge Tube Co.,Ltd

Add:Zouqu Town Industrial Zone, Wujin Changzhou City, Jiangsu, China Tel: 0519-83631254 Fax: 0519-83631533 Email: jiangnan@jiangnan-cn.cn




Electrical Characteristics

	Type: 3R600AL4		
DC spark-over voltage		600	V
		±20	%
Impulse spark-over voltage			
at $100V/\mu s$ - for 99% of measured values		<1100	V
-typical values of distribution		<1000	V
at 1 kV/ μ s - for 99% of measured values		<1400	V
- typical values of distribution		<1200	V
Service life			
10 operations	50Hz, 1s	10	A
10 operations $[5x (+) \& 5x(-)]$	$8/20\mu s$	20	kA
1 operations	$8/20\mu s$	25	kA
1 operations	$10/350 \mu s$	1	KA
300 operations $[5x (+)\&5x(-)]$	$10/1000 \mu s$	200	A
Insulation resistance at 250 Vdc		>10	GΩ
Capacitance at 1 MHz		<1.5	pF
Arc voltage at 1 A		~15	V
Glow to arc transition current		~0.6	A
Glow voltage		~70	V
Weight		~2.0	g
Operation and storage temperature		-40+125	°C
Marking, blue			[
		☞ 3R600	
		3R -Two Electrode 600 -Nominal voltage	



·Dimensional drawing



3R-AL4 Type (ϕ 8 \times 10)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Gas Discharge Tubes - GDTs / Gas Plasma Arrestors category:

Click to view products by ZOUGUANG manufacturer:

Other Similar products are found below:

M51-A90X PMT1023004 PMT1040004 CG2800 GTCR37-231M-R10 WPGT-2N145B6L WPGT-2N230B6L WPGT-2N470B6L WPGT-2RM230A6L WPGT-2RM350A6L WPGT-2RM70A6L WPGT-2RM90A6L WPGT-2S145 WPGT-2S350 WPGT-2S470 WPGT-3R350CF WPGT-3R350G1 WPGT-3R90G1 WPGT-3R75G1 WPGT-3R470G1 WPGT-3R250C WPGT-3R230G1 WPGT-2S230 WPGT-2RM145A6L WPGT-2R1000B8L WPGT-2N70B6L WPGT-2N350B6L WPGT-2N230B6L1 CG2145 T61-C350X 9071.99.0547 (73_Z-0-0-547) B88069X6940B152 RF1219-000 A9L16618 RF2339-000 9071.99.0052(73_Z-0-0-52) 9071.99.0054 CG32.7L CG6400SM CG6470SM CG7250MS CG7400MS SPBT12-280/1 SPCT2-280/3 SPCT2-280/4 T2 20KA 4P 2003-09-SM-RPLF 2026-07-A1 2026-25-C3 2039-80-BLF